



Manufacturer's Certification Napco Window Systems Replacement Windows

Ply Gem Windows, located at 4415 Pheasant Ridge Road, Suite 300, Roanoke, Virginia 24014, manufactures certain Napco Window Systems exterior windows and doors that, when purchased with optional Low-E glass and argon gas fill in a double or triple glazed unit, meet or exceed the prescriptive criteria established by the IECC for all climate zones in which the window or doors are installed.

To qualify for the Energy Improvement and Extension Act tax credit, exterior windows and doors must have both a U-Factor rating of .30 or lower and a Solar Heat Gain Coefficient (SHGC) rating of .30 or lower. The Napco Window Systems exterior window and door products set forth in Attachment A have a U-Factor and SHGC of .30 or below and qualify for this tax credit. To qualify for the tax credit, homeowners must purchase the qualifying Napco Window Systems exterior window and door products and install in accordance with Ply Gem Windows' instructions between January 1, 2009 and December 31, 2010.

To certify the qualifying Napco Window Systems products for purposes of the tax credits available under the Energy Improvement and Extension Act of 2008, **Ply Gem Windows represents that its window and door products having a U-Factor and SHGC of .30 or below as set forth in Attachment A are "Eligible Building Envelope Component(s)" that qualify for the federal income tax credit allowed under the Energy Improvement and Extension Act of 2008.**

Homeowners should consult their tax advisor to determine whether they qualify for any potential income tax credits.

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

A handwritten signature in black ink, appearing to read 'Lynn Morstad'.

Lynn Morstad
President, Ply Gem Windows

June, 2009



3500



ATTACHMENT A

Product Type / Popular Glazing Options	U-Factor (Center of Glass)	R-value (Center of Glass)	Total Unit R-value	NFRC Certified Values					ENERGY STAR QUALIFIED
				NFRC CPD Number	Total Unit U-Factor	SHGC	VT	CR	
Double Hung				PGW-M-29					
Double Low E Argon IGU	0.25	4.0	3.3		0.30	0.27	0.47	53	Yes
Grids (Width<1")	0.25	4.0	3.3		0.30	0.24	0.42	53	Yes
Triple Pane Double Low E Argon IGU	0.18	5.6	4.2		0.24	0.24	0.42	61	Yes
Grids (Width<1")	0.18	5.6	4.0		0.25	0.22	0.38	61	Yes
Reinforced & Insulated Sash Option				PGW-M-32					
Energy Package (Low E Argon IGU)	0.26	3.8	3.3		0.30	0.29	0.53	52	Yes
Grids (Width<1")	0.26	3.8	3.3		0.30	0.26	0.47	52	Yes
Energy Package Plus (Double Low E Argon IGU)	0.25	4.0	3.4		0.29	0.27	0.47	53	Yes
Grids (Width<1")	0.25	4.0	3.4		0.29	0.24	0.42	53	Yes
Energy Package Max (Triple Pane Double Low E Argon IGU)	0.18	5.6	4.3		0.23	0.25	0.43	62	Yes
Grids (Width<1")	0.18	5.6	4.2	0.24	0.22	0.38	62	Yes	
Slider				PWG-M-38					
Low E Argon IGU	0.26	3.8	3.3		0.30	0.28	0.52	54	Yes
Double Low E Argon IGU	0.25	4.0	3.3		0.30	0.26	0.47	55	Yes
Grids (Width<1")	0.25	4.0	3.3		0.30	0.24	0.41	55	Yes
Triple Pane Double Low E Argon IGU	0.18	5.6	4.2		0.24	0.24	0.42	61	Yes
Grids (Width<1")	0.18	5.6	4.0	0.25	0.22	0.38	61	Yes	
Reinforced & Insulated Sash Option				PWG-M-37					
Energy Package (Low E Argon IGU)	0.26	3.8	3.3		0.30	0.28	0.52	54	
Energy Package Plus (Double Low E Argon IGU)	0.25	4.0	3.4		0.29	0.26	0.46	55	Yes
Grids (Width<1")	0.25	4.0	3.4		0.29	0.24	0.41	55	Yes
Energy Package Max (Triple Pane Double Low E Argon IGU)	0.18	5.6	4.2		0.24	0.24	0.42	61	Yes
Grids (Width<1")	0.18	5.6	4.2	0.24	0.22	0.38	61	Yes	
Picture				PWG-M-41					
Low E Argon IGU Grids (Width<1")	0.26	3.8	3.6		0.28	0.29	0.54	56	Yes
Double Low E Argon IGU	0.26	3.8	3.7		0.27	0.30	0.54	56	Yes
Grids (Width<1")	0.26	3.8	3.7		0.27	0.27	0.48	56	Yes
Triple Pane Double Low E Argon IGU	0.16	6.3	5.1		0.20	0.28	0.49	65	Yes
Grids (Width<1")	0.16	6.3	5.0	0.20	0.25	0.44	65	Yes	



3500



ATTACHMENT A

				NFRC Certified Values					
Product Type / Popular Glazing Options	U-Factor (Center of Glass)	R-value (Center of Glass)	Total Unit R-value	NFRC CPD Number	Total Unit U-Factor	SHGC	VT	CR	ENERGY STAR QUALIFIED
Casement									
Low E Argon IGU	0.26	3.8	3.4	PWG-M-25	0.29	0.27	0.50	58	Yes
Grids (Width<1")	0.26	3.8	3.4		0.29	0.25	0.45	58	Yes
Double Low E Argon IGU	0.25	4.0	3.4		0.29	0.25	0.44	59	Yes
Grids (Width<1")	0.25	4.0	3.4		0.29	0.23	0.40	59	Yes
Triple Pane Double Low E Argon IGU	0.18	5.6	4.3		0.23	0.23	0.40	65	Yes
Grids (Width<1")	0.18	5.6	4.3		0.23	0.21	0.36	65	Yes
Fixed Casement									
Low E Argon IGU Grids (Width<1")	0.26	3.8	3.7	PWG-M-24	0.27	0.28	0.52	58	Yes
Double Low E Argon IGU	0.25	4.0	3.7		0.27	0.29	0.51	59	Yes
Grids (Width<1")	0.25	4.0	3.7		0.27	0.26	0.46	59	Yes
Triple Pane Double Low E Argon IGU	0.18	5.6	4.8		0.21	0.27	0.47	65	Yes
Grids (Width<1")	0.18	5.6	4.8		0.21	0.24	0.42	65	Yes
Awning									
Low E Argon IGU	0.26	3.8	3.4	PWG-M-26	0.29	0.27	0.50	55	Yes
Grids (Width<1")	0.26	3.8	3.4		0.29	0.25	0.45	55	Yes
Double Low E Argon IGU	0.25	4.0	3.4		0.29	0.25	0.44	56	Yes
Grids (Width<1")	0.25	4.0	3.4		0.29	0.23	0.40	56	Yes
Triple Pane Double Low E Argon IGU	0.18	5.6	4.3		0.23	0.23	0.40	66	Yes
Grids (Width<1")	0.18	5.6	4.3		0.23	0.21	0.36	66	Yes
Premium Sliding Patio Door (CMPD)									
Low E Argon IGU	0.26	3.8	3.4	PWG-M-45	0.29	0.27	0.49	57	Yes
Grids (Width<1")	0.26	3.8	3.4		0.29	0.23	0.43	57	Yes
Double Low E Argon IGU	0.26	3.8	3.6		0.28	0.25	0.44	58	Yes
Grids (Width<1")	0.26	3.8	3.6		0.28	0.22	0.38	58	Yes
Triple Pane, Double Low E Argon IGU	0.17	5.9	4.5		0.22	0.23	0.40	64	Yes
Grids (Width<1")	0.17	5.9	4.3		0.23	0.20	0.34	64	Yes

NFRC (National Fenestration Rating Council)

- CPD - Certified Product Directory
- SHGC - Solar Heat Gain Coefficient
- VT - Visible Light Transmission
- CR - Condensation Resistance

U-Factor - Rate of Heat Loss
 R-Value - Resistance to Heat Flow

Footnotes: Total unit values: Single strength glass for all dual & triple pane windows with and w/o grids.
 Total unit values: Double strength glass for all dual & triple pane Patio Doors and Picture Windows.



2500



ATTACHMENT A

					NFRC Certified Values				
Product Type / Popular Glazing Options	U-Factor (Center of Glass)	R-value (Center of Glass)	Total Unit R-value	NFRC CPD Number	Total Unit U-Factor	SHGC	VT	CR	ENERGY STAR QUALIFIED
				PWG-M-42					
Picture Low E Argon IGU Grids (Width<1")	0.26	3.8	3.4		0.30	0.29	0.54	56	Yes
				PWG-M-25					
Casement Low E Argon IGU Grids (Width<1")	0.26	3.8	3.5		0.29	0.27	0.50	58	Yes
	0.26	3.8	3.5		0.29	0.25	0.45	58	Yes
				PWG-M-24					
Fixed Casement Low E Argon IGU Grids (Width<1")	0.26	3.8	3.6		0.28	0.28	0.52	58	Yes
				PWG-M-26					
Awning Low E Argon IGU Grids (Width<1")	0.26	3.8	3.4		0.29	0.25	0.48	54	Yes
	0.26	3.8	3.4		0.29	0.23	0.43	54	Yes

NFRC (National Fenestration Rating Council)

- CPD - Certified Product Directory
- SHGC - Solar Heat Gain Coefficient
- VT - Visible Light Transmission
- CR - Condensation Resistance

U-Factor - Rate of Heat Loss
R-Value - Resistance to Heat Flow

Footnotes: Total unit values: Single strength glass for all dual & triple pane windows with and w/o grids.
 Total unit values: Double strength glass for all dual & triple pane Patio Doors and Picture Windows.